

Product Summary

D-Link Out-Door Enclosure's designed for outdoor weather conditions. Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bent, welded and Powder coated with highest quality standards as per the required Outdoor Standards.

Configuration for standard Racks are Welded frame integrated with side walls and down vented top cover, Fan mounting provision on the Front Door for water & dust resistance, rear side of the Enclosure having Pole mounting provision, front glass door with lock and Key provides the security

Outdoor Pole-Mount Enclosures are available in 6U to 12U Variants with 400mm/450mm/500mm depths as per the customer requirements.

Width 550mm.



Features:

- **Conforms to IP55 Outdoor Standards**
- Adjustable 19" equipment mounting verticals provide the better mounting flexibility maximizing the usable mounting space
- Depth adjustable mounting slots
- Precision engineering capabilities and best efficient software configuration product technology provides the best product quality and fastest delivery in the industry
- Top Panel with ventilation and cable entry from the Bottom
- Cooling fans mounted on Front Door with Top cover for Rain Water & Dust resistance.
- Powder coated finish with pretreatment process meeting all industry standards
- Pole mounting Provision on the Rear Side
- 100% assured compatibility with all equipment conforming to DIN 41494. General industrial standard for equipment

Technical Data:

Rack Standard	:	Conforms to IP55 standard
Construction	:	Welded
Front Door	:	Lockable Steel Door
Basic Frame	:	Steel
Equipment Mounting	:	DIN Standard Slots
Mounting Angle	:	19" Mounting angles made of formed steel
Standard Finish	:	Powder Coated
Top and Bottom Cover	:	Welded to Frame, Field Cable entry exit from bottom
Standard Color	:	Grey
Static Load	:	20+ kgs

Part Code & Dimensions:

Part Code	Height OD	Height Usable	Width	Usable	Depth	Usable
	in mm (H)	in U (H)	In mm(W)	Width(W)	In mm(D)	In mm(D)
NWR-9U-5550-GR-IP55	480	9U	550	19"	500	400

Technical BOM:

D-Link Part No	Description
NWR-9U-5550-GR-IP55	<p>IP 55 Outdoor Pole Rack 9U X 550mm W X 500mm D</p> <p>Construction of Material- 1.2/1.5mm Thick CRCA sheet</p> <p><u>Each Enclosure includes:</u></p> <p>A very compact design, welded structure with front accessible</p> <p>The side panels are integrated type & welded with canopy & bottom cover</p> <p>Rigid frame that can be fixed to the pole</p> <p>Front Door with Filter, Louver & Lock</p> <p>90CFM, 230V AC Fan - 2 Nos, front door</p> <p>Self adhesive thermal foam from inside</p> <p>Door Hinges - 2 Nos</p> <p>Cable Glands at bottom side for cable entry</p> <p>19" Angles 9U - 2 Nos for equipment mounting</p> <p>Gasket (As per IP55 Standard)</p> <p>Pole Mounting Brackets at rear side- 2 Nos</p> <p>Hood For Air Inlet at front side</p> <p>Powder Coated Surface</p> <p>3 Socket PDU 5 Amp - 1 NO.</p> <p>Finish : Light Grey -RAL 7035-powder coated</p>