

Product Summary

D-Link Floor Standing Steel Enclosure's designed for Servers, Networking, Data Centres, Audio Video, Telecom and Lab applications. Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bended, welded and Powder coated with highest quality standards.

Configuration for standard Unloaded Racks are welded frame with 4 pillars of Multi Fold profile welded to top and bottom panels. 2 Pair Depth rails to additionally support the Enclosure. Removable side panels in 650 & above depth Racks partially vented for better air circulation. Openings/Cut outs for field cable entry from Top & Bottom of the Rack. Vented top cover with fan mounting provision, Front Glass door with lock and key. Rear Vented, metal door with lock and key. Free Floor standing Design with 4 No. castor wheels.

Racks are available in 17U to 42U Variants with 600mm/650mm/800mm/1000mm depth and 600 and 800 width configurations.



Features:

- **Conforms to DIN 41494 OR equivalent ISO Standards**
- Adjustable 19" equipment mounting verticals provide the better mounting flexibility maximizing the usable mounting space
- Depth adjustable mounting slots
- Precision engineering capabilities and best efficient software configuration product technology provides the best product quality and fastest delivery in the industry
- Top and bottom Panel with ventilation and cable entry facility
- Provision to mount the cooling fans on the top panel
- Powder coated finish with pretreatment process meeting all industry standards
- Grounding and Bonding Options
- 100% assured compatibility with all equipment conforming to DIN 41494. General industrial standard for equipment

Part Code & Dimensions:

Part Code	Height OD	Height Usable	Height Usable	Width	Usable	Depth	Usable
	In mm(H)	in mm (H)	in U (H)	In mm(W)	Width(W)	In mm(D)	In mm(D)
NFR-17U-6060-BL-SK	954	756	17U	600	19"	600	520
NFR-17U-6080-BL-SK	954	756	17U	600	19"	800	720
NFR-22U-6060-BL-SK	1176	978	22U	600	19"	600	520
NFR-22U-6080-BL-SK	1176	978	22U	600	19"	800	720
NFR-24U-6065-BL-SK	1265	1067	24U	600	19"	650	570
NFR-24U-6080-BL-SK	1265	1067	24U	600	19"	800	720
NFR-24U-6010-BL-SK	1265	1067	24U	600	19"	1000	920
NFR-24U-8080-BL-SK	1265	1067	24U	800	19"	800	720
NFR-24U-8010-BL-SK	1265	1067	24U	800	19"	1000	920
NFR-27U-6065-BL-SK	1398	1200	27U	600	19"	650	570
NFR-27U-6080-BL-SK	1398	1200	27U	600	19"	800	720
NFR-27U-6010-BL-SK	1398	1200	27U	600	19"	1000	920
NFR-27U-8080-BL-SK	1398	1200	27U	800	19"	800	720
NFR-27U-6010-BL-SK	1398	1200	27U	600	19"	1000	920
NFR-27U-8010-BL-SK	1398	1200	27U	800	19"	1000	920
NFR-32U-6065-BL-SK	1620	1422	36U	600	19"	650	570
NFR-32U-6080-BL-SK	1620	1422	36U	600	19"	800	720
NFR-32U-6010-BL-SK	1620	1422	36U	600	19"	1000	920
NFR-32U-8080-BL-SK	1620	1422	36U	800	19"	800	720
NFR-32U-8010-BL-SK	1620	1422	36U	800	19"	1000	920
NFR-36U-6065-BL-SK	1798	1600	36U	600	19"	650	570
NFR-36U-6080-BL-SK	1798	1600	36U	600	19"	800	720
NFR-36U-6010-BL-SK	1798	1600	36U	600	19"	1000	920
NFR-36U-8080-BL-SK	1798	1600	36U	800	19"	800	720
NFR-36U-8010-BL-SK	1798	1600	36U	800	19"	1000	920
NFR-42U-6065-BL-SK	2070	1867	42U	600	19"	650	570
NFR-42U-6080-BL-SK	2070	1867	42U	600	19"	800	720
NFR-42U-6010-BL-SK	2070	1867	42U	600	19"	1000	920
NFR-42U-8080-BL-SK	2070	1867	42U	800	19"	800	720
NFR-42U-8010-BL-SK	2070	1867	42U	800	19"	1000	920
NFR-42U-8010-BL-SK-HSD	2070	1867	42U	800	19"	1000	920
NFR-42U-8010-BL-SK-HFSR	2070	1867	42U	800	19"	1000	920
NFR-42U-6012-BL-SK	2070	1867	42U	600	19"	1200	1120
NFR-42U-8012-BL-SK	2070	1867	42U	800	19"	1200	1120

Technical Data:

Rack Standard	:	Conforms to DIN 41494 or equivalent standard
Construction	:	Welded Frame
Front Door	:	Lockable Toughened Glass Door, Steel Single, Steel Dual
Basic Frame	:	Steel
Equipment Mounting	:	DIN Standard 10mm Sq. Slots / Direct M6 Tap
Mounting Angle	:	19" Mounting angles made of formed steel
Standard Finish	:	Powder Coated
Top and Bottom Cover	:	Welded to Frame, Vented and Field Cable entry exit cut outs
Mounting Option	:	Castor wheels (Front 2 wheels with Brakes and rear without brakes) Or Levelers Or Base plinth
Standard Color	:	Black or Grey
Static Load	:	500+ Kgs.

Standard Accessories:

- Front & Rear Door
- Side Panels
- Power Distribution Units.
- Cable Manager.
- Fans and Fan Modules.
- Hardware Packet
- Jacking Feet

Orderable Accessories:

- Fixed Shelf
- Sliding Shelf
- Key Board Shelf
- Cantilever Shelf
- Support Angles
- Cable Basket
- Rack Grouting Kit