

## Product Summary

D-Link Wall Mount Enclosures specially designed for small networking, domestic applications, Audio, Video, Telecom and Lab applications.

Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bended, welded and powder coated with highest quality standards.

Configuration for standard Enclosures are:

Welded frame integrated with side walls and vented top cover with fan mounting provision, rear side of the Enclosure having wall mounting provision, front glass door with lock and Key provides the visibility and security.

Wall Mount Enclosures are available in 4U to 15U Variants with 400mm/450mm/500mm/600mm depth. Width 550mm.



## Features:

- Conforms to DIN 41494 OR equivalent ISO Standards
- Adjustable 19" equipment mounting verticals provide better mounting flexibility and maximizes the usable mounting space
- Depth adjustable mounting slots
- Precision engineering capabilities and best efficient software configuration product technology provide the best product quality and fastest delivery in the industry
- Top and bottom Panel with ventilation and cable entry facility
- Provision to mount cooling fans on the top panel
- Powder coated finish with pretreatment process meeting all industry standards
- Grounding and Bonding Options. 100% assured compatibility with all equipment conforming to DIN 41494 (General industrial standard for equipment)

## Technical Data:

<b>Rack Standard</b>	:	<b>Conforms to DIN 41494 or equivalent standard</b>
<b>Construction</b>	:	<b>Welded</b>
<b>Front Door</b>	:	<b>Lockable Toughened Glass Door</b>
<b>Basic Frame</b>	:	<b>Steel</b>
<b>Equipment Mounting</b>	:	<b>DIN Standard Slots</b>
<b>Mounting Angle</b>	:	<b>19" Mounting angles made of formed steel</b>
<b>Standard Finish</b>	:	<b>Powder Coated</b>
<b>Top and Bottom Cover</b>	:	<b>Welded to Frame, Vented and Field Cable entry exit cut outs</b>
<b>Standard Color</b>	:	<b>Grey</b>
<b>Static Load</b>	:	<b>Up to 40 Kgs</b>

## Part Code & Dimensions:

Part Code	Height OD	Height Usable	Height Usable	Width	Usable	Depth	Usable
	In mm(H)	in mm (H)	in U (H)	In mm(W)	Width(W)	In mm(D)	In mm(D)
NWR-15U-5560-GR-CPD	747	667	15U	550	19"	600	550

## Technical BOM:

Part code	Description
NWR-15U-5560-GR-CPD	<p><b>Wall Mount 15U x 550 W x 600 D - Grey Color</b>                      Front Glass Door (tinted, Toughened) with Lock &amp; Key,                      2 pairs of 19" Mounting Rails with U-Marking                      Welded Side Walls with Metal Engraved D-Link Logo.</p> <p><b>Standard Accessories:</b>                      1U Cable Manager (1), Hardware Pkt of 20 (1 Pkt)                      4 Socket 5 Amp. 2 Socket 5/15 Amp Power Distribution Unit (1 No)                      Roof Mounted Fan Unit / 90 CFM /230V AC (2 Nos)</p>

### Standard Accessories:

- Power Distribution Units.
- 1U Horizontal Cable Manager.
- Fan
- Hardware Packet

### Orderable Accessories:

- Cantilever Tray
- 2U Horizontal Cable Manager
- Hardware Packet