

Cat5E UTP Patch Cords

D-Link Cat5e patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA-568-C.2 standard. These patch cords are appropriate for high speed data transmission



SPECIFICATIONS

- Conductor: **24 AWG, Multi-strands**
- Conductor Metal: **Bare Copper**
- Insulation Material: **HD-PE**
- Material: **FR-PVC**
- Heat Resistance: **75oC max**
- Flame Property: **The purpose of the vertical flame test is to screen out flammable wires. It follows the CM standards**
- Insertion Cycles: **750 times**

MODULAR CONNECTOR/PLUG

- RJ-45 8P for transparent color
- Gold Plated: **03MU°**
- Contact Blade: **Copper Alloy**
- Temperature Range:- **-20° C ~ 75° C**
- Dielectric withstanding voltage: **1000V DC/min, < 0.5A**
- Insulation Resistance: **> 500MΩ, 100V DC/min**
- UL Applications: **PC UL94-V-0**

Application

- 100BASE-TX Fast Ethernet, 1000BASE-T
- Power over Ethernet (PoE)

ORDERING INFORMATION

CAT5E Patch Cord	
Part Code	Description
NCB-5EUBLUR1-1	Cat5E UTP 24AWG Patch Cord, 1M
NCB-5EUBLUR1-2	Cat5E UTP 24AWG Patch Cord, 2M
NCB-5EUBLUR1-3	Cat5E UTP 24AWG Patch Cord, 3M
NCB-5EUBLUR1-5	Cat5E UTP 24AWG Patch Cord, 5M



D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2018 D-Link Corporation. All rights reserved. Release 01 (May 2018)