

Cat6 UTP Patch Cords

D-Link Cat6 patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA-568-C.2 standard. These patch cords are appropriate for high speed data transmission.

Approval: UL Listed  and ETL Verified



SPECIFICATIONS

- Conductor: **24 AWG, Multi-strands**
- Conductor Metal: **Bare Copper**
- Insulation Material: **HDPE**
- Outer Jacket: **FR-PVC**
- Heat Resistance: **60 ° C**
- Insertion Cycles: **750 times**

Application

100BASE-TX Fast Ethernet, 1000BASE-T,
Power over Ethernet (PoE)

MODULAR CONNECTOR/PLUG

RJ-45 8P for transparent color

- Gold Plated: **03MU°**
- Contact Blade: **Copper/Alloy**
- Temperature Range: **-20° to 75° C**
- Dielectric withstanding voltage: **1000V DC/ min < 05A**
- Insulation Resistance: **> 500 MΩ, 1000 DC/Min**
- UL Applications: **PC UL94-V-0**

ORDERING INFORMATION

CAT6 Patch Cord	
Part Code	Description
NCB-C6UXXXR1-Y	Cat6 UTP 24AWG Patch Cord. XXX stands for color options and Y denotes length



D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2017 D-Link Corporation. All rights reserved. Release 01 (May 2017)